

Recommended P.C.B Layout

MATERIAL


Insulator : 30% Glass fiber PBT
Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP
Insulation Resistance : 5000MΩMin. at DC 500V
Contact Resistance : 20mΩMax. at DC 100mA
Dielectric Voltage : AC 500V for one minute
Operation Temperature : -40°C to + 105°C

510-7 0- 06 G B 00
1 2 3 4

1. No. of contacts
2. G: Gold flash
S: Selective
T: Tin plated
3. B: Black Insulator
W: White Insulator
4. Pinrex internal code.

				TOLERANCE				OLD PART NO. BH1S-06GB		TITLE BOX HEADER 2.54*2.54mm, STRAIGHT TYPE, (GP)			
				.0 =±.30		UNITS : mm		DRAWER 尹小姜		CHECK			
				.00 =±.20				SHEET 1 OF 1		REV. A			
				.000 =±.XXX				SCALE NONE		APP'D		DRAW NO. 510-70-06GB00(B版)	
B 修改开口		2011/12/19		.0000=±.				SIZE A4		NEW PART NO. 510-70-06GB00			
A RELEASE		2004/05/12		ANG.=±3'									
REV.		DESCRIPTION		DATE									